

## Liberty - Biscuit

### Product Description

Infuse your room with contemporary charm by installing one of our deluxe carpets from the Liberty range. Expertly made from durable polyester, our Liberty carpets are hardwearing and easy to maintain with their durable twist pile design. They also benefit from being bleach cleanable so you can be confident in your purchase. Featuring a plush 14mm pile height and hardwearing fusion backing, this carpet is both comfortable underfoot and ideal for those high-traffic areas around the home. Boasting a stunning range of contemporary colours, the Liberty range will style perfectly with any decor!



| Range Details        | Properties                 | Technical Data       | Technical Specification |
|----------------------|----------------------------|----------------------|-------------------------|
| Construction         | 100% Polyester             | Fire Certification   | Cfl                     |
| Pile Type            | Twist                      | Water Fastness       | 4                       |
| Primary Backing      | Woven Polypropylene        | Light Fastness       | 5                       |
| Secondary Backing    | Woven Polypropylene Fleece | Slip Resistance      | NPD                     |
| Pile Height (mm)     | 14mm                       | Machine Guage        | 1/8                     |
| Total Height (mm)    | 17mm                       | Tuft Density         | 25/6                    |
| Pile Weight (gr/m2)  | 1628                       | Tog Rating           | 2.35                    |
| Total Weight (gr/m2) | 2480                       | Bleach Cleanable     | Yes                     |
| Roll Width (m)       | 2.5, 4, 5                  | VOC Emissions Rating | Low Emissions           |
| Pattern Measurement  | N/A                        |                      |                         |
| Country of Origin    | United Kingdom             |                      |                         |

| Installation Guidance            | Properties                             |
|----------------------------------|--|
| Recommended Underlay             | Super 10mm Underlay                    |
| Suitable for Underfloor Heating? | Yes - combined tog must not exceed 2.5 |

### Room Suitability

