

## Sydney - Raven

## **Product Description**

The Sydney range is a high-quality luxurious saxony carpet. The carpet is made using 100% Polypropylene, which is then woven into a solid action backing - providing a solid yet very soft construction, feeling great underfoot whilst also protecting against the rising cold underneath. The Sydney range is available in a wide variety of colours, making it suitable for any room in the home. This product is equipped with action back, making the carpet easy to work with and ensuring long-lasting strength and quality.



| Range Details        | Properties          | Technical Data              | Technical Specification |
|----------------------|---------------------|-----------------------------|-------------------------|
| Construction         | 100% Polyester      | Fire Certification          | Cfl-S1                  |
| Pile Type            | Saxony              | Water Fastness              | ≥ 3-4                   |
| Primary Backing      | Woven Polypropylene | Light Fastness              | ≥5                      |
| Secondary Backing    | FusionBac           | Slip Resistance             | ≥0.30                   |
| Pile Height (mm)     | 17mm                | Machine Guage               | 1/8th                   |
| Total Height (mm)    | 19.5                | Tog Rating                  | 1.7                     |
| Pile Weight (gr/m2)  | 1,900 gr/m2         | Thermal Resistance          | 0.17                    |
| Total Weight (gr/m2) | 2610                | Bleach Cleanable            | Yes                     |
| Roll Width (m)       | 4 & 5               | <b>VOC Emissions Rating</b> | Low (Within Limit)      |
| Pattern Measurement  | N/A                 |                             |                         |
| Country of Origin    | Belgium             |                             |                         |

| Installation Guidance            | Properties                             |  |
|----------------------------------|--|--|
| Recommended Underlay             | High Density 9mm Underlay              |  |
| Suitable for Underfloor Heating? | Yes - combined tog must not exceed 2.5 |  |

## **Room Suitability**













