

## Herringbone - Warm Vanilla Oak

### Product Description

Achieve effortless contemporary style with our range of Herringbone vinyl flooring, a fantastic budget alternative to solid wood. Our Herringbone range comes equipped with a cushioned foam backing, which helps reduce the effects of subfloor imperfections, removing the need for any underlay. The durable 2.8mm thickness and 0.2mm wear layer means this vinyl range is designed to withstand the comings and goings of a busy household, whilst keeping scratches and scuffs to a minimum. Suitable to be laid on top of underfloor heating, our Herringbone vinyl range is ideal for most rooms around the home, offering an impressive 0,25 W/m.K thermal conductivity rating and 18dB acoustical insulation. The herringbone style of this range will add a touch of sophistication to any room, while also providing a water-resistant floor that is easy to maintain.



Range Details	Properties	Technical Data	Technical Specification
Construction	PVC Foam	Fire Certification	Cfl-s1
Backing	Foam backing	Slip Resistance	R10
Thickness (mm)	2.8	Acoustical Insulation	18dB
Total Weight (gr/m <sup>2</sup> )	1600	Thermal Conductivity	0,25 W/m.K
Roll Width (m)	2m, 3m & 4m	Thermal Resistance	0,0112 m <sup>2</sup> /Kw
Wear Layer (mm)	0.2	Resistance to Household Chemicals	Yes
Recyclable?	100%	Static Electricity Propensity	EN 1815
Pattern Repeat Measurement	100cm x 199cm	Formaldehyde Rating	E1
Tile/Plank Measurement	45.5cm x 9cm	VOC Emissions Rating	ISO 16000
Country of Origin	Belgium		

Installation Guidance	Properties
Recommended Adhesive	Impero Vinyl Adhesive
Suitable for Underfloor Heating?	Yes

Warranty Type	Years
Residential	5

### Room Suitability

