

Natural Rustic Oak - Smooth Lacquered

Product Description

Our Natural Rustic Oak is a quality engineered wood floor that is as durable as it is beautiful with its light brown hues that add a welcoming feel to many rooms in your home. With an expertly brushed and oiled 3mm solid top layer ensure Natural Rustic Oak will keep its timeless looks for years to come, this flooring is designed to offer great stability and durability even in the busiest areas.



Range Details	Properties	Technical Data	Technical Specification
Finish	Smooth Lacquered	Fire Certification	Dfl-S1
Species	Oak	Slip Resistance	0.4-0.6
Grade	Rustic	Thermal Conductivity	
Veneer	3mm	Wear Resistance	5000rEN 660-
Thickness	14mm	PCP Content	PCP < 5 x 10- 6n
Board Width	150mm	Formaldehyde Rating	â%0,008 mg/m3
Board Length	300 - 1200mm	VOC Emissions Rating	â%0 5 ppm
Pack Coverage	1.44m2		
Boards per Pack	8pcs		
Wood Origin	Europe		

Installation Guidance	Properties
Fitting System	Tongue & Groove
Recommended Underlay	Timberlay Silver
Expansion Gap	10 mm
Suitable For Underfloor Heating?	Yes
Acclimatisation Time	48-72 Hours

Room Suitability

