

## Manhattan Frozen Oak Brushed & Lacquered

### Product Description

Are you looking for a showstopper? Look no further! Our popular Manhattan Frozen Oak can bring the look and feel of solid wood flooring into your home, with all the strength and durability only engineered wood flooring has, at a fraction of the cost of solid wood. Manhattan Frozen Oak will astound, delivering reliability and peace of mind, this stunning engineered wood flooring will be a perfect fit for homes in need of a modern and naturally beautiful floor. The cool grey shades with darker undertones will compliment any décor in your home. A truly stunning engineered wood floor, with a contemporary appeal and charm, this wonderful wood will tick all your boxes.



| Range Details   | Properties           | Technical Data       | Technical Specification    |
|-----------------|----------------------|----------------------|----------------------------|
| Finish          | Brushed & Lacquered  | Fire Certification   | Dfl-S1                     |
| Species         | Oak                  | Slip Resistance      | NPD                        |
| Grade           | Rustic               | Thermal Conductivity | 0,16W/mK                   |
| Veneer          | 3mm                  | Wear Resistance      | USRV22                     |
| Thickness       | 14mm                 | PCP Content          | Not Detected               |
| Board Width     | 180mm                | Formaldehyde Rating  | E1 (0,2mg/m3)              |
| Board Length    | 300 - 1200mm         | VOC Emissions Rating | Test Method: YC/T 207-2014 |
| Pack Coverage   | 1.72 8m <sup>2</sup> |                      |                            |
| Boards per Pack | 8                    |                      |                            |
| Wood Origin     | France               |                      |                            |

| Installation Guidance            | Properties        |
|----------------------------------|-------------------|
| Fitting System                   | Tongue and Groove |
| Recommended Underlay             | Timberlay Gold    |
| Expansion Gap                    | 10 mm             |
| Suitable For Underfloor Heating? | Yes               |
| Acclimatisation Time             | 48 Hours          |

### Room Suitability

