

## Marylebone - Champagne Oak

### Product Description

Do you want quality flooring that will become a conversation piece? Champagne Oak Brushed Lacquered engineered wood floor brings a rustic touch into your home, creating a warm and welcoming atmosphere at the same time. The 2.5mm solid wood veneer boasts light brown hues and honey accents to brighten any room, while the rustic-grade grain provides the perfect counterpoint to modern furnishings. The planks measure 14mm in thickness and 130mm in width, to suit smaller or larger rooms in equal measure. Brushed to enhance the textures and natural beauty of the solid wood layer, the surface also features a high-quality lacquered finish to provide stain and scratch protection which is easy to install with the click system. This flooring is only suitable for underfloor heating, when glued down completely. Otherwise for a floating installation, only the first row needs to be glued. Checkout our accessories section,



Range Details	Properties	Technical Data	Technical Specification
Finish	Brushed & Lacquered	Fire Certification	Dfl-S1
Species	Oak	Slip Resistance	NPD
Grade	Prime	Thermal Conductivity	0.14W/mK
Veneer	2.5mm	Wear Resistance	WR1
Thickness	14mm	PCP Content	not detected
Board Width	130mm	Formaldehyde Rating	E-1
Board Length	725mm	VOC Emissions Rating	340 ug/m3
Pack Coverage	0.65m2		
Boards per Pack			
Wood Origin	Europe		

Installation Guidance	Properties
Fitting System	Optilock
Recommended Underlay	Timberlay Gold
Expansion Gap	10 mm
Suitable For Underfloor Heating?	Yes
Acclimatisation Time	48 Hours

### Room Suitability

