

## Mayfair Sandy Oak

### Product Description

Quality, reliable, and spectacular best reflects our range of engineered wood floors. With gorgeous honey undertones with contrasting darker knots, the Mayfair Sandy Oak is as beautiful as it is durable and versatile. The lacquered finish not only protects the wood but offers more visual depth and complexity. The solid 14mm thickness and easy click fitting system, this engineered floor can be fitted with ease and will make a striking addition to any room.



Range Details	Properties	Technical Data	Technical Specification
Finish	Lacquered	Fire Certification	Dfl-s1
Species	Oak	Slip Resistance	62 USRV
Grade	Prime	Thermal Conductivity	0.14 W/mK
Veneer	2.5mm	Wear Resistance	n/a
Thickness	14mm	PCP Content	not detected
Board Width	180mm	Formaldehyde Rating	E1
Board Length	2200mm	VOC Emissions Rating	A+
Pack Coverage	2.77m <sup>2</sup>		
Boards per Pack	7pcs		
Wood Origin	Poland		

Installation Guidance	Properties
Fitting System	Click
Recommended Underlay	Timberlay Silver
Expansion Gap	10 mm
Suitable For Underfloor Heating?	Yes
Acclimatisation Time	48 Hours

### Room Suitability

