

Chelsea Chevron - Golden Oak

Product Description

Golden tones, eye-catching grain, organic lines, and subtle colour variations give this floor a charming rustic appearance. Chelsea Chevron comes with natural beauty with function. It comes with a tough 2.5mm top layer and a 14mm thickness, offering stability underfoot and durability at the same time. The brushed lacquered finish acts as a protective layer against everyday wear, transforming cleaning into a fuss-free task. Easy to install with the 4V Click system, this engineered wood floor will suit even the busies areas of a family home. The floor is also compatible with underfloor heating, enhancing both the elegance and the comfort of your living spaces.



Range Details	Properties	Technical Data	Technical Specification
Finish	Brushed & Lacquered	Fire Certification	Dfl-s1
Species	Oak	Slip Resistance	48
Grade	Character	Thermal Conductivity	0.14 W/mK
Veneer	2.5mm	Wear Resistance	WR1 > (P2000)
Thickness	14mm	PCP Content	not detected
Board Width	130mm	Formaldehyde Rating	E-1
Board Length	725mm	VOC Emissions Rating	340 ug/m3
Pack Coverage	0.61 m ²		
Boards per Pack	8 pcs. x 725mm		
Wood Origin	Europe		

Installation Guidance	Properties
Fitting System	Tongue and Groove
Recommended Underlay	Timberlay Gold
Expansion Gap	10 mm
Suitable For Underfloor Heating?	Yes
Acclimatisation Time	48 Hours

Room Suitability

